

PATENT ABSTRACTS OF JAPAN

(11)Publication number : 64-054749
(43)Date of publication of application : 02. 03. 1989

(51)Int. Cl.
H01L 23/28
H01L 21/60
H01L 23/50


(21)Application number : 62-211993
(22)Date of filing : 26. 08. 1987
(71)Applicant : MATSUSHITA ELECTRIC IND CO LTD
(72)Inventor : KITAHIRO ISAMU
KONDO SHUJI
KIKUCHI TATSUO
TAKASE YOSHIHISA

(54) SEMICONDUCTOR DEVICE AND MANUFACTURE THEREOF

(57)Abstract:

PURPOSE: To obtain a highly accurate and highly reliable semiconductor device by placing a semiconductor chip through an insulating substrate on one group of highly accurate metal leads, connecting the leads to fine metal wirings, and transfer molding them.

CONSTITUTION: A thin resin plate 3 is attached to leads 1 having protrusions 6, and electrodes on a semiconductor chip 4 are connected to the leads 1 by fine metal wirings 5. Then, the leads except the protrusions 6 are sealed with resins 2, 7, shape and size are determined and cut. According to this structure, a small-sized and thin semiconductor device having high dimensional accuracy and reliability is obtained without complicated structure like a both-side substrate only by employing metal leads of special shape at part, and is preferably adapted for an IC.



LEGAL STATUS

[Date of request for examination]
[Date of sending the examiner's decision of rejection]
[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]
[Date of final disposal for application]
[Patent number]
[Date of registration]
[Number of appeal against examiner's decision of rejection]